



 **TECHNICAL SPECIFICATION**

Aluminium extrusions providing a high quality and aesthetically pleasing finish.

Lightweight panels which are approximately 1/3 of the weight of steel panels of similar form.

Panels in lengths of up to 7.3m long by nominal 1m wide.

A range of profiles available in depths ranging from 19mm to 89mm.

Retains high residual value and the aluminium is fully recyclable.

A selection of load bar heights to accommodate a wide variety of spans and load conditions (for full load span and load bearing data, please visit our Downloads page and download our full Techdek brochure).

A feature can be made of the panels by anodising or powder coating.

Structural efficiency is achieved by passing the swage bar through the load bar without cutting into the top or bottom edge thus providing a panel of great rigidity and strength.

 **CLEANING & MAINTENANCE INSTRUCTIONS**

FLOORING GRILLES & MILL FINISH ALUMINIUM HANDRAILS CLEANING & MAINTENANCE INSTRUCTIONS

1. The "GRILLE and HANDRAILING" is manufactured from aluminium alloy, and is supplied in "MILL FINISHED" condition. As such, the material is virtually maintenance-free and does not require any special treatment.
2. Cleaning of all exposed parts should be carried out periodically by the use of Detergent/Cleaning solutions of low Alkalinity followed by rinsing.
3. DO NOT USE any abrasive cleaning agents, acids or caustics.
4. Should the surface become damaged specialist attention will be required in order to repair or replace.

LOUVREDEK & BRISE SOLEIL

1. The system is manufactured from aluminium alloy, finished in a "Mill" condition. As such, the material is virtually maintenance free and does not require any special treatment.
2. Cleaning of all exposed parts should be carried out periodically by the use of Detergent/Cleaning solutions of low Alkalinity followed by rinsing.
3. DO NOT USE any abrasive cleaning agents, acids or caustics.

continued overleaf 





CLEANING & MAINTENANCE INSTRUCTIONS continued

LOUVREDEK & BRISE SOLEIL FLOORING

1. The system is manufactured from aluminium alloy, finished in an 'Anodised' condition. As such, the material is virtually maintenance free and does not require any special treatment.
2. Cleaning of all exposed parts should be carried out periodically by the use of Detergent/Cleaning solutions of low Alkalinity followed by rinsing.
3. DO NOT USE any abrasive cleaning agents, acids or caustics.

POWDER COATED FLOORING GRILLES

1. Cleaning of all exposed parts should be carried out periodically by the use of Detergent/Cleaning solutions of low Alkalinity followed by rinsing.
2. DO NOT USE any abrasive cleaning agents, acids or caustics.
3. Should the surface become damaged specialist attention will be required in order to repair or replace.



neaco

norton engineering alloys co ltd

balustrade | balconies | flooring | grilles | bathing

www.neaco.co.uk

